

Tubing, Mechanical Protection and Fittings Certified for Canada - Component

[See General Information for Tubing, Mechanical Protection and Fittings Certified for Canada - Component](#)

CP SYSTEM CO LTD

E191879

27-37 JEONGGWANSANGGOK 1-GIL JEONGGWAN-EUP GIJANG-GUN
 BUSAN, 46018 REPUBLIC OF KOREA

Cat. No.	Max Working Temp, °C	Indoor Use	Outdoor Use	FT-4
Mechanical protection tubing				
CPS Series - CPS-10*, CPS-12*, CPS-16*, CPS-22*, CPS-28*, CPS-36*, CPS-48*	105	Yes	-	-
PAH Series - PAH-10*, PAH-12*, PAH-16*, PAH-22*, PAH-28*, PAH-36*, PAH-48*	60	Yes	-	-
PAHT Series - PAHT-22*, PAHT-28*, PAHT-36*, PAHT-48*	105	Yes	-	-
PART Series - PART-22+, PART-28+, PART36+, PART-48+	105	Yes	-	-
RAH Series - RAH-07B, RAH-10B, RAH-12B, RAH-16B, RAH-22B, RAH-28B, RAH-36B, RAH-48B				
	105	Yes	-	-


Cat. No.	Indoor Dry Locations	Liquid-tight Locations
90 degree elbow fittings		
Metric Thread - PAC-M10*, PAC-M12*, PAC-M202*, PAC-M16*, PAC-M22*, PAC-M28*, PAC-M36*, PAC-M48*		
	Yes	-
Metric Thread - PWC-M107*, PWC-M10*, PWC-M12*, PWC-M202*, PWC-M16*, PWC-M22*, PWC-M28*, PWC-M36*, PWC-M48*		
	Yes	-
Metric Thread - TWC-M10*, TWC-M12*, TWC-M202*, TWC-M16*, TWC-M22*, TWC-M28*, TWC-M36*, and TWC-M48*.		
	Yes	-
PF Thread - PAC-G10*, PAC-G12*, PAC-G16*, PAC-G22*, PAC-G28*, PAC-G36*, PAC-G42*, PAC-G48*		
	Yes	-
PF Thread - PWC-G10*, PWC-G12*, PWC-G16*, PWC-G22*, PWC-G28*, PWC-G368*, PWC-G36*, PWC-G42*, PWC-G48*		
	Yes	-

Feedback

PF Thread - TWC-G10*, TWC-G12*, TWC-G16*, TWC-G22*, TWC-G28*, TWC-G368*, TWC-G36*, TWC-G42* and TWC-G48*.	Yes	-
PG Thread - PAC-P09*, PAC-P110*, PAC-P130*, PAC-P11*, PAC-P136*, PAC-P16*, PAC-P21*, PAC-P29*, PAC-P36*, PAC-P48*	Yes	-
PG Thread - PWC-P077*, PWC-P097*, PWC-P09*, PWC-P110*, PWC-P130*, PWC-P11*, PWC-P132*, PWC-P162*, PWC-P136*, PWC-P16*, PWC-P163*, PWC-P22*, PWC-P29*, PWC-P36*, PWC-P48*	Yes	-
PG Thread - TWC-P09*, TWC-P110*, TWC-P130*, TWC-P11*, TWC-P132*, TWC-P162*, TWC-136*, TWC-P16*, TWC-P163*, TWC-P21*, TWC-P29*, TWC-P36*, TWC-P48*	Yes	-
Straight fittings		
Metric Thread - PNC-M107*, PNC-M127*, PNC-M167*, PNC-M10*, PNC-M120*, PNC-M20*, PNC-M102*, PNC-M12*, PNC-M202*, PNC-M126*, PNC-M16*, PNC-M226*, PNC-M22*, PNC-M3222*, PNC-M28*, PNC-M4028*, PNC-M36*, PNC-M5036*, PNC-M48*, PNC-M6348*	Yes	-
Metric Thread - TNC-M10*, TNC-M120*, TNC-M20*, TNC-M102*, TNC-M12*, TNC-M202*, TNC-M126*, TNC-M16*, TNC-M226*, TNC-M22*, TNC-M3222*, TNC-M28*, TNC-M4028*, TNC-M36*, TNC-M5036* and TNC-M48*.	Yes	-
NPT Thread - PNC-N10*, PNC-N12*, PNC-N16*, PNC-N22*, PNC-N28*	Yes	-
NPT Thread - TNC-N10*, TNC-N12*, TNC-N16*, TNC-N22* and TNC-N28*.	Yes	-
PF Thread - PNC-G07*, PNC-G10*, PNC-G12*, PNC-G16*, PNC-G22*, PNC-G28*, PNC-G36*, PNC-G42*, PNC-G48*	Yes	-
PF Thread - TNC-G10*, TNC-G12*, TNC-G16*, TNC-G22*, TNC-G28*, TNC-G36*, TNC-G42* and TNC-G48*.	Yes	-
PG Thread - PNC-P077*, PNC-P097*, PNC-P117*, PNC-P137*, PNC-P070*, PNC-P09*, PNC-P110*, PNC-P130*, PNC-P160*, PNC-P0912*, PNC-P11*, PNC-P132*, PNC-P162*, PNC-P136*, PNC-P16*, PNC-P216*, PNC-P163*, PNC-P22*, PNC-P29*, PNC-P36*, and PNC-P48*	Yes	-
PG Thread - TNC-P09*, TNC-P110*, TNC-P130*, TNC-P160*, TNC-P0912*, TNC-P11*, TNC-P132*, TNC-P162*, TNC-P136*, TNC-P16*, TNC-P216*, TNC-P163*, TNC-P21*, TNC-P29*, TNC-P36*, TNC-P48*	Yes	-

* - Add suffix B or G to indicate the color of the tubing or fitting, black or gray.

+ - Add suffix B or Y to indicate the color of the tubing, black or yellow

Marking: Company name, catalog designation, temperature rating and the Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2020-06-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."