

# PNCCCL IP68



- 재 질 : 고품질 폴리아미드 6 (PA6)
- 방 수 등 급 : IP68 (EN 60529)
- 적 용 온 도 범 위 : -40°C ~ +105°C
- 순 간 최 대 온 도 : +150°C
- 자 기 소 화 성 : UL94-HB, 할로겐/카드뮴 발생 없음
- 색 상 : 검정, 회색
- 적 용 : 철도차량, 공작기계, 산업기계, 자동화기계, 조선소 등  
기계의 진동으로 발생하는 케이블의 단선을 방지하기 위해 사용되는 커넥터

## 제품사이즈




### PF Thread (JIS B0202)

(단위 : mm)

검정	회색	나사(inch)	튜브사이즈	Øi(최소)	Øi(최대)	S	L1	L	ØD	SW1	SW2
PNCCCL-G10B	PNCCCL-G10G	G1/2	10	3.5	6.5	20.4	9.0	70.6	24.2	19.7	22.6
PNCCCL-G12B	PNCCCL-G12G	G1/2	12	4.0	8.0	20.4	9.0	72.0	27.6	22.8	25.5
PNCCCL-G16B	PNCCCL-G16G	G1/2	16	7.0	12.3	20.4	9.0	75.2	33.0	28.0	25.5

# PNCCCL IP68



## Metric Thread (EN 60423)

(단위 : mm)

검정	회색	나사	튜브사이즈	Øi(최소)	Øi(최대)	S	L1	L	ØD	SW1	SW2
PNCCCL-M10B	PNCCCL-M10G	M12 X 1.5	10	3.5	6.5	11.8	9.0	71.3	24.2	19.7	22.6
PNCCCL-M120B	PNCCCL-M120G	M16 X 1.5	10	3.5	6.5	15.8	9.0	70.5	24.2	19.7	22.6
PNCCCL-M102B	PNCCCL-M102G	M12 X 1.5	12	4.0	7.1	11.8	9.0	72.5	27.6	22.8	25.5
PNCCCL-M12B	PNCCCL-M12G	M16 X 1.5	12	4.0	8.0	15.8	9.0	72.5	27.6	22.8	25.5
PNCCCL-M162B	PNCCCL-M162G	M20 X 1.5	12	4.0	8.0	19.8	9.0	72.5	27.6	22.8	25.5
PNCCCL-M126B	PNCCCL-M126G	M16 X 1.5	16	7.0	10.9	15.8	9.0	75.8	33.0	28.0	25.5
PNCCCL-M16B	PNCCCL-M16G	M20 X 1.5	16	7.0	12.3	19.8	9.0	75.5	33.0	28.0	25.5
PNCCCL-M216B	PNCCCL-M216G	M25 X 1.5	16	7.0	12.3	24.7	9.0	70.8	33.0	28.0	25.5

## Pg Thread (DIN 40430)

(단위 : mm)

검정	회색	나사	튜브사이즈	Øi(최소)	Øi(최대)	S	L1	L	ØD	SW1	SW2
PNCCCL-P09B	PNCCCL-P09G	Pg09	10	3.5	6.5	14.9	9.0	70.8	24.2	19.7	22.6
PNCCCL-P092B	PNCCCL-P092G	Pg09	12	4.0	8.0	14.9	9.0	67.5	27.6	22.8	25.5
PNCCCL-P11B	PNCCCL-P11G	Pg11	12	4.0	8.0	18.3	9.0	72.4	27.6	22.8	25.5
PNCCCL-P132B	PNCCCL-P132G	Pg13.5	12	4.0	8.0	20.2	9.0	66.4	27.6	22.8	25.5
PNCCCL-P162B	PNCCCL-P162G	Pg16	12	4.0	8.0	22.3	9.0	66.4	27.6	22.8	25.5
PNCCCL-P116B	PNCCCL-P116G	Pg11	16	7.0	12.3	18.3	9.0	71.5	33.0	28.0	25.5
PNCCCL-P13B	PNCCCL-P13G	Pg13.5	16	7.0	12.3	20.2	9.0	71.5	33.0	28.0	25.5
PNCCCL-P16B	PNCCCL-P16G	Pg16	16	7.0	12.3	22.3	9.0	70.8	33.0	28.0	25.5