

SPNC IP68

※ 가스켓 & Lock-Nut 포함



- 재 질 : 고품질 폴리아미드 6 (PA6) + 황동니켈도금
- 방 수 등 급 : IP68 (EN 60529)
- 적용 온도 범위 : -40°C ~ +105°C
- 순간 최대 온도 : +150°C
- 자 기 소 화 성 : UL94-HB, 할로젠/카드뮴 발생 없음
- 색 상 : 검정, 회색
- 적 용 : 철도차량, 공작기계, 산업기계, 자동차기계, 조선소 등

제품사이즈



Pg Thread (DIN 40430)

(단위 : mm)

검정	회색	나사	튜브사이즈	S	L1	L	Øi	ØD	SW
SPNC-P09B	SPNC-P09G	Pg09	10	15.1	14.0	47.5	9.8	24.6	19.7
SPNC-P11B	SPNC-P11G	Pg11	12	18.5	14.0	47.1	14.0	27.6	22.8
SPNC-P132B	SPNC-P132G	Pg13.5	12	20.3	14.0	47.1	15.0	27.6	22.8
SPNC-P136B	SPNC-P136G	Pg13.5	16	20.3	14.0	49.0	15.1	33.0	28.0
SPNC-P16B	SPNC-P16G	Pg16	16	22.4	14.0	49.0	15.1	33.0	28.0
SPNC-P21B	SPNC-P21G	Pg21	22	28.2	16.0	59.7	22.0	43.2	37.5
SPNC-P29B	SPNC-P29G	Pg29	28	36.8	16.0	65.7	30.5	48.8	43.0
SPNC-P36B	SPNC-P36G	Pg36	36	46.8	20.0	81.4	36.0	60.6	52.2
SPNC-P48B	SPNC-P48G	Pg48	48	59.3	22.0	86.2	52.4	71.9	64.0

Metric Thread (EN 60423)

(단위 : mm)

검정	회색	나사	튜브사이즈	S	L1	L	Øi	ØD	SW
SPNC-M10B	SPNC-M10G	M12 X 1.5	10	11.9	14.0	47.5	7.5	24.6	19.7
SPNC-M1610B	SPNC-M1610G	M16 X 1.5	10	15.9	14.0	47.5	9.8	25.0	19.7
SPNC-M12B	SPNC-M12G	M16 X 1.5	12	15.9	14.0	47.1	12.0	27.6	22.8
SPNC-M2012B	SPNC-M2012G	M20 X 1.5	12	19.9	14.0	47.1	15.0	27.6	22.8
SPNC-M16B	SPNC-M16G	M20 X 1.5	16	19.9	14.0	49.0	15.1	33.0	28.0
SPNC-M2516B*	SPNC-M2516G*	M25 X 1.5	16	24.9	16.0	55.6	20.5	33.0	28.0
SPNC-M22B	SPNC-M22G	M25 X 1.5	22	24.9	16.0	59.7	20.5	43.2	37.5
SPNC-M3222B	SPNC-M3222G	M32 X 1.5	22	31.9	16.0	59.7	22.0	43.2	37.5
SPNC-M28B	SPNC-M28G	M32 X 1.5	28	31.9	16.0	67.8	27.0	48.8	43.0
SPNC-M36B	SPNC-M36G	M40 X 1.5	36	39.9	20.0	81.4	33.0	60.6	42.2
SPNC-M48B	SPNC-M48G	M50 X 1.5	48	49.9	22.0	86.2	42.0	71.9	64.0