

TICG IP67



- 재 질 : 고품질 폴리아미드 6 (PA6)
- 방 수 등 급 : IP 67 (EN 60529)
- 적 용 온 도 범 위 : -40°C ~ +105°C
- 순 간 최 대 온 도 : +150°C
- 자 기 소 화 성 : UL94-HB, 할로젠/카드뮴 발생 없음
- 색 상 : 검정, 회색
- 적 용 : 분전함, 제어함, 통신함 또는 각종 전기기기로부터 케이블을 인출할 때 사용하는 커넥터 방수, 방진, 방유구조가 확실하고 내절연, 내충격 및 난연성이 뛰어난 커넥터

제품사이즈



UNE Thread (ASME B1.1)

(단위 : mm)

검정	회색	나사	헬사이즈	S	Øi(최소)	Øi(최대)	L1	L	ØO	ØD	SW1	SW2
TICG-U1010B	TICG-U1010G	1/2-28UNEF	8S, 10S	13.0	3.5	7.0	10.0	43.9	17.4	25.4	22.6	18.0
TICG-U1210B	TICG-U1210G	5/8-24UNEF	10SL, 12S	15.0	3.5	7.0	10.0	43.9	19.6	25.4	22.6	18.0
TICG-U1410B	TICG-U1410G	3/4-20UNEF	14, 14S	18.0	3.5	7.0	10.0	43.9	23.0	25.4	22.6	18.0
TICG-U1610B	TICG-U1610G	7/8-20UNEF	16, 16S	21.0	3.5	7.0	10.0	43.9	27.0	25.4	22.6	18.0
TICG-U1810B	TICG-U1810G	1-20UNEF	18	24.0	3.5	7.0	10.0	43.9	30.0	25.4	22.6	18.0
TICG-U2010B	TICG-U2010G	1 3/16-18UNEF	20, 22	28.5	3.5	7.0	10.0	43.9	34.5	25.4	22.6	18.0
TICG-U1212B	TICG-U1212G	5/8-24UNEF	10SL, 12S	15.0	4.0	8.9	10.0	46.2	19.6	28.5	25.5	20.6
TICG-U1412B	TICG-U1412G	3/4-20UNEF	14, 14S	18.0	4.0	8.9	10.0	46.2	23.0	28.5	25.5	20.6
TICG-U1612B	TICG-U1612G	7/8-20UNEF	16, 16S	21.0	4.0	8.9	10.0	46.2	27.0	28.5	25.5	20.6
TICG-U1812B	TICG-U1812G	1-20UNEF	18	24.0	4.0	8.9	10.0	46.2	30.0	28.5	25.5	20.6
TICG-U2012B	TICG-U2012G	1 3/16-18UNEF	20, 22	28.5	4.0	8.9	10.0	46.2	34.5	28.5	25.5	20.6
TICG-U2812B	TICG-U2812G	1 7/16-18UNEF	24, 28	35.0	4.0	8.9	10.0	46.2	41.0	28.5	25.5	20.6
TICG-U1616B	TICG-U1616G	7/8-20UNEF	16, 16S	21.0	7.0	13.4	10.0	47.2	27.0	28.5	25.5	25.5
TICG-U1816B	TICG-U1816G	1-20UNEF	18	24.0	7.0	13.4	10.0	47.2	30.0	28.5	25.5	25.5
TICG-U2016B	TICG-U2016G	1 3/16-18UNEF	20, 22	28.5	7.0	13.4	10.0	47.2	34.5	28.5	25.5	25.5
TICG-U2816B	TICG-U2816G	1 7/16-18UNEF	24, 28	35.0	7.0	13.4	10.0	47.2	41.0	28.5	25.5	25.5
TICG-U2222B	TICG-U2222G	1 3/16-18UNEF	20, 22	28.5	12.0	19.6	10.0	53.4	34.5	37.6	34.0	34.0
TICG-U2822B	TICG-U2822G	1 7/16-18UNEF	24, 28	35.0	12.0	19.6	10.0	53.4	41.0	37.6	34.0	34.0
TICG-U3222B	TICG-U3222G	1 3/4-18UNS	32	43.0	12.0	19.6	10.0	53.4	49.0	49.0	34.0	34.0
TICG-U2828B	TICG-U2828G	1 7/16-18UNEF	24, 28	35.0	18.0	26.5	10.0	53.4	41.2	48.5	43.0	42.2
TICG-U3228B	TICG-U3228G	1 3/4-18UNS	32	43.0	18.0	26.5	10.0	53.4	49.0	48.0	43.0	42.2
TICG-U3628B	TICG-U3628G	2-18UNS	36	49.5	18.0	26.5	10.0	53.4	55.7	48.0	43.0	42.2
TICG-U3636B	TICG-U3636G	2-18UNS	36	49.5	22.0	39.8	10.0	63.7	55.7	58.5	52.5	52.0